




ENERG
енергия · ενεργεια




NIBE

NIBE F1355-43



55 °C

35 °C



A+++

A+++



47 dB



dB

■ 42
■ **42**
■ 42
kW

■ 45
■ **45**
■ 45
kW




2019

811/2013




ENERG



енергия · ενέργεια



NIBE





NIBE F1355-43






A scale of energy efficiency classes represented by arrows pointing right, from top to bottom: A+++ (green), A++ (light green), A+ (yellow-green), A (yellow), B (orange), C (red-orange), D (red), E (dark red), F (red), G (red). A black arrow pointing left with 'A+++' is positioned to the right of the top of the scale.

+ 
 + 
 + 
 + 

Supplier's name:	NIBE AB		
Model:	NIBE F1355-43		
Temperature application	35	55	°C
Declared load profile for water heating			
Seasonal space heating energy efficiency class, average climate:	A+++	A+++	
Water heating energy efficiency class, average climate:			
Rated heat output, average climate:	45	42	kW
Annual energy consumption for space heating, average climate	18588	21700	kWh
Annual electricity consumption for water heating, average climate			kWh
Seasonal space heating energy efficiency, average climate:	192	152	%
Water heating energy efficiency, average climate:			%
Sound power level LWA indoors	47		dB
Rated heat output, cold climate:	45	42	kW
Rated heat output, warm climate:	45	42	kW
Annual energy consumption for space heating, cold climate	21011	24977	kWh
Annual electricity consumption for water heating, cold climate			kWh
Annual energy consumption for space heating, warm climate	11463	13776	kWh
Annual electricity consumption for water heating, warm climate			kWh
Seasonal space heating energy efficiency, cold climate:	203	158	%
Water heating energy efficiency, cold climate:			%
Seasonal space heating energy efficiency, warm climate:	202	155	%
Water heating energy efficiency, warm climate:			%
Sound power level LWA outdoors	-		dB

Data for package fiche

Controller class	II		
Controller contribution to efficiency	2		%
Seasonal space heating energy efficiency of package, average climate:	194	154	%
Seasonal space heating energy efficiency class for package, average climate:	A+++	A+++	%
Seasonal space heating energy efficiency of package, cold climate:	205	160	%
Seasonal space heating energy efficiency of package, warm climate:	204	157	%

Model(s):		NIBE F1355-43							
Type of heat source/sink:		Brine/water							
Low-temperature heat pump:		No							
Equipped with supplementary heater:		No							
Heat pump combination heater:		No							
Climate condition:		Average							
Temperature application:		Medium temperature (55 °C)							
Applied standards: EN14825 - EN12102-1									
Rated heat output		Prated	42,0	kW	Seasonal space heating energy efficiency		η_s	152	%
<i>Declared capacity for part load at outdoor temperature Tj</i>				<i>Declared coefficient of performance for part load at outdoor temperature Tj</i>					
Tj = -7 °C	Pdh	36,5	kW	Tj = -7 °C	COPd	3,1			
Tj = +2 °C	Pdh	26,6	kW	Tj = +2 °C	COPd	3,9			
Tj = +7 °C	Pdh	13,3	kW	Tj = +7 °C	COPd	4,7			
Tj = +12 °C	Pdh	7,8	kW	Tj = +12 °C	COPd	5,4			
Tj = biv	Pdh	40,1	kW	Tj = biv	COPd	2,8			
Tj = TOL	Pdh	40,1	kW	Tj = TOL	COPd	2,8			
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)	COPd				
Bivalent temperature				T _{biv}	-10	°C	Operation limit temperature		
Cycling interval capacity for heating				P _{cyh}		kW	Cycling interval efficiency		
Degradation co-efficient				Cdh	1,00	-	Heating water operating limit		
							WTOL	65	°C
<i>Power consumption in modes other than active mode</i>				<i>Supplementary heater</i>					
Off mode	P _{OFF}	0,008	kW	Rated heat output		P _{sup}	0,0	kW	
Thermostat-off mode	P _{TO}	0	kW	Type of energy input		Electric			
Standby mode	P _{SB}	0,008	kW						
Crankcase heater mode	P _{CK}	0,02	kW						
<i>Other items</i>									
Capacity control		Variable		Rated air flow rate, outdoors				m ³ /h	
Sound power level, indoors/outdoors		L _{WA}	47/-	dB	Rated water flow rate, indoor heat exchanger				
Annual energy consumption		Q _{HE}	21700	kWh	Rated brine or water flow rate, outdoor heat exchanger		5,92	m ³ /h	
<i>For heat pump combination heater:</i>									
Declared load profile				Water heating energy efficiency		η_{wh}		%	
Daily electricity consumption		Q _{elec}		kWh	Daily fuel consumption		Q _{fuel}	kWh	
Annual electricity consumption		AEC		kWh	Annual fuel consumption		AFC	GJ	
Approved by:									
Contact details		© NIBE Energy Systems - Box 14 - Hannabadvägen 5 - 28521 Markaryd - Sweden							